



# 10 Gigabit Copper SFP+ Transceiver Module

10GBase-T (RJ45) Port, 30 m (98 ft.), up to 10 Gbps Data-Transfer Rate with Cat6a Cabling

Part No.: 508179

EAN-13: 0766623508179 | UPC: 766623508179

## 10 Gigabit Copper SFP+ Transceiver Module

The new line of Intellinet Network Solutions Enhanced Small Form Factor Pluggable (SFP+) Transceivers provides customers with a combination of high-performance and affordability. The metal housing of these transceiver modules reduces electromagnetic interference and increases their durability.

## 10 Gigabit Ethernet connections via Copper RJ45 Cabling

The Intellinet Network Solutions 10 Gigabit Copper SFP+ Transceiver Module provides an impressive data transfer speed of up to 10 Gigabits per second when using Cat6a (augmented Cat6 cabling with improved specifications). This SFP+ copper transceiver is an extremely versatile and ultra-high performing connection point for your server or workstation.

## State-of-the-Art NBASE-T™ Technology

With full support of the IEEE 802.3bz standard, the Intellinet Network Solutions 10 Gigabit Copper SFP+ Transceiver Module supports Gigabit speeds using Cat6 and Cat5e network cabling. The former transfers and receives data at up to 5 Gbps whereas the latter still manages an impressive 2.5 Gbps.

## Compatibility

Compatibility in your network is essential. The Intellinet Network Solutions SFP+

## INTELLINET®

#### intellinet-network.com

Transceiver Module can be used with any Intellinet Network Solutions SFP+ equipped network switch or any other MSA-compliant (multi-source agreement) SFP+ enabled switch. And since the Intellinet Network Solutions SFP+ transceiver module is set to broadcast the part number MA-SFP-10G-T, compatibility to your Cisco gear is provided.

## **Hot-Pluggable**

The Intellinet Network Solutions 10 Gigabit Copper SFP+ Optical Transceiver Module is fully hot-pluggable, allowing you to install the module without rebooting your network switch for uninterrupted network traffic.

#### **Features:**

- Provides cost-effective and reliable 10 Gigabit Ethernet connections over copper
- Up to 10 Gbps data-transfer rate with Cat6a network cable
- Up to 5 Gbps with Cat6 and 2.5 Gbps with Cat5e network cable
- Adds a 10 Gigabit Ethernet copper connection to a network switch or media converter that supports SFP+ transceivers
- RJ45 port with Auto MDI/MDI-X support
- Equivalent to the Cisco MA-SFP-10G-T transceiver
- Fits any Intellinet Gigabit Ethernet switch with SFP+ module slots or any MSA-compliant SFP+ port
- Compliant with the SFP Multi-Source Agreement (MSA)
- Maximum transfer distance of 30 m (98 ft.) at 10 Gbps over Cat6a network cable
- Maximum transfer distance of 50 m (164 ft.) at 5 Gbps over Cat6 cable and at 2.5 Gbps over Cat5e cable
- Maximum transfer distance of 100 m (328 ft.) at 100 Mbps over Cat5e network cable
- Low EMI due to fully metallic housing
- SFP+ standard form factor
- Supports hot-plugging
- Fully NDAA-compliant
- Three-Year Warranty

## **Specifications:**

#### Standards

- IEEE 802.3ab (1000Base-T Gigabit Ethernet)
- IEEE 802.3an (10 Gigabit Ethernet over Cat6a Twisted-pair Copper)
- IEEE 802.3bz (2.5 Gbps over Cat5, 5 Gbps over Cat6 Twisted-pair Copper)

#### General

## INTELLINET®

### intellinet-network.com

- Media support:
- 1000Base-T Cat5e or higher UTP/STP RJ45
- 2.5GBASE-T Cat5e or higher UTP/STP RJ45
- 5GBASE-T Cat6 or higher UTP/STP RJ45
- 10GBASE-T Cat6a or higher UTP/STP RJ45
- Connector: RJ45 SFP port
- Distance: 30 m (98 ft.) at 10 Gbps over Cat6a
- Design: SFP+ (enhanced small form-factor pluggable)
- Certifications: FCC Class A, CE Mark, IEC-60825, RoHS, NDAA

#### Compatible Brands

• Cisco, Intellinet Network Solutions, ZyXEL, Linksys, TP-Link, Ubiquiti, D-Link, Edimax, Allnet, Allied Telesis, Digitus, KTI Networks, LevelOne, PLANET, Tenda, TRENDnet, ZTE, Avaya, Mikrotik, Enterasys, Finisar, Dell Force10, Riverstone, Fortinet and more

#### Power

- Power requirement: 3.3 V
- Power consumption: 3.0 W (maximum)

#### Environmental

- Dimensions: 68 (L) x 13.7 (W) x 13.6 (H) [mm] / 2.68 (L) x 0.54 (W) x 0.54 (H) [in]
- Weight: 25 g (0.9 oz.)
- Operating temperature: 0 60°C (32 140°F)
- Storage temperature: -40 85°C (-40 185°F)
- Operating humidity: 5 95% RH, non-condensing

#### Package Contents

• 10 Gigabit Copper SFP+ Transceiver Module





## intellinet-network.com



