



# 10GBase-T to 10GBase-R Media Converter

1 x 10 GB SFP+ Slot, 1 x 10GB RJ45 Port

Part No.: 508193

EAN-13: 0766623508193 | UPC: 766623508193

The Intellinet Network Solutions 10GBase-T to 10GBase-R Media Converter offers the network designer a device for migration from copper-based Ethernet to Fiber Ethernet. Now, migration or expansion of existing networks can be achieved with minimum cost and complexity. The converter is completely transparent to the network, so the network performs exactly the way it did before, only now it can support both copper and fiber media. And with a super-fast 10 Gbps connection, network speed stays constant for high-bandwidth data transfers.

## Expand the size of an existing network.

The 10GBase-T to 10GBase-R Media Converter provides fiber connectivity to Ethernet segments, allowing for even greater networking expansion between extended workgroups. It also provides building-to-building connectivity without the need for the cost and disruption associated with the installation of additional routers.

## Enhance the distance between networking devices.

Connecting the converter to fiber segments further extends distances between network nodes, offering increased spatial and distance options for networks where none existed before.

## Cabling Flexibility

Network managers can install fiber cabling anywhere within a network without

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

changing the arrangement of their copper-based Ethernet. The compact size of the converter allows it to be easily deployed in any narrow desktop location or to be used in a wall-mount installation. Several converters can be simultaneously installed into a 19" rackmountable chassis, providing much-needed flexibility for networks.

## Features:

- One 10 GB RJ45 port — maximum distance of 100 m (300 ft.)
- One 10 GB SFP+ port (requires transceiver, separately available from Intellinet Network Solutions)
- Supports IEEE802.3u, 10GBase-T and 10GBase-FL
- Supports full-duplex mode or half-duplex mode operation with autonegotiation
- Status LEDs for power and Link/TX for both ports
- Supports jumbo frames up to 9 kBytes
- External 12 VDC power adapter
- Fully NDAA-compliant
- Three-year warranty

## Specifications:

### Standards

- 1000Base-T, 2.5GBase-T, 5GBase-T, 10GBase-T
- 1000Base-X, 2500Base-X, 5GBase-R, 10GBase-R

### General

- Media support:
  - 1000Base-T: Cat5 UTP/STP, max. 100 m (330 ft.)
  - 2.5GBase-T: Cat5e UTP/STP, max. 50 m (164 ft.)
  - 5GBase-T: Cat5e UTP/STP, max. 50 m (164 ft.)
  - 10GBase-T: Cat6a UTP/STP, max. 50 m (164 ft.)
- Connectors:
  - One RJ45 port, 10GBase-T
  - One SFP+ port, 10GBase-FL
- Certifications: FCC, CE, RoHS, UKCA, NDAA

### LEDs

- Power
- LINK/ACT for RJ45 port
- LINK/ACT for SFP+ port
- 10G Indicator
- Optical signal input LED

### Power

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- External power adapter: 12 VDC, 0.5 A
- Power consumption: 5 watts (maximum)

#### Environmental

- Metal housing
- Dimensions: 95 (L) x 70 (W) x 25 (H) [mm] / 3.74 (L) x 2.76 (W) x 0.98 (H) [in]
- Weight: 0.2 g (0.44 lb.)
- Operating temperature: 0 - 55°C (32 - 131°F)
- Operating humidity: 5 - 80% RH, non-condensing
- Storage temperature: -10 - 70°C (14 - 158°F)

#### Package Contents

- 10GBase-T to 10GBase-R Media Converter
- External power adapter
- User manual



