

Net Toner and Probe Kit

Tone Generator, Tests Datacom, Telecom, Security, Video, and Audio Networks

Part No.: **515566**

EAN-13: 0766623515566 | UPC: 766623515566

Features:

- Tests datacom, telecom, security, video, and audio networks
- Two position switch for single or multi-tone signal
- LEDs for line polarity, continuity and voltage
- Enhanced talk battery mode provides power for voice communications over inactive pairs
- Testing leads and modular cables for individual wire tests or modular jack tests
- Replaceable plastic tip to prevent accidental shorts
- Trace or identify wire or cables in a bundle or group
- Alligator clips, RJ45 jack, RJ12 plug, optional F-connector
- Three-year warranty

Specifications:

Net Toner

- Toner Frequency: High alternating 500-781 Hz ; Low alternating 446-657 Hz
- Talk Battery: 9V into a 600 ohms circuit
- Voltage protection: 50 VDC or 24 VAC
- Battery: 9V DC standard or alkaline
- CE Approved: EN 55022 Class B for ITE and EN 55024
- Size: 125 (L) x 68 (W) x 26 (H) mm (4.9 x 2.7 x 1.2 in.)
- Weight: 120g (.37 lb)

Net Probe

- Gain: 30 db
- Tip resistance: 30 ohms (Plastic tip)
- Battery: 9V DC standard or alkaline
- CE Approved: EN 55022 Class B for ITE and EN 55024
- Size: 210 (L) x 40 (W) x 28 (H) mm (8.1 x 1.6 x 1 in.)
- Weight: 140g (.30 lb)

Environmental:

- Operating temperature: 0 – 40°C (32 – 104°F)

Package Contents

- Net Probe
- Net Toner w/ Alligator clips and RJ12 connector

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Female F-connector to RJ45 adapter
- Carrying pouch
- User Manual



