



Adjustable 19" Rackmount DIN Rail Kit, 2U

Chassis to Mount Top Hat DIN Rail Equipment in a 19 in. Rack,
Adjustable Rail Depth of 48 to 174 mm (1.9 to 6.9 in.), Aluminum,
Black RAL 9005

Part No.: 716345

EAN-13: 0766623716345 | UPC: 766623716345

Depth-Adjustable DIN Rail Rack-Mount Kit to Easily Mount Your Top Hat Equipment in a 19-inch Cabinet

The Adjustable 19" Rackmount DIN Rail Kit, 2U from Intellinet Network Solutions allows for seamless integration of your top hat DIN rail equipment into a 19 in. network enclosure, open frame rack or server cabinet.

Tailor Your Space with Depth Adjustment

With eight adjustable levels ranging from 48 to 174 mm (1.89 to 6.85 in.), it accommodates a wide spectrum of products. Whether it's industrial PoE switches, media converters, power supplies, circuit breakers, terminal blocks, or more – this kit adapts to your needs.

Compliant and Compatible

Meeting EIA 310 / IEC 60297 standards, it fits into all standard 19 in. / 482.6 mm racks. The DIN-rail, in accordance with IEC/EN 60715 standards, ensures a perfect fit for your equipment.

Durable Construction Built to Last

Crafted with heavy-duty anodized 2 mm thick aluminum, our kit is built to withstand the test of time. It offers great strength and stability, providing a maximum load capacity of 9 kg (20 lbs.).

Everything You Need Included

We've got you covered with a package that includes four M6x12 screws, four M6 cage nuts, and four M6 plastic washers for 19" mounting straight out of the

box.

Features:

- Rack-mountable chassis with top hat DIN rail to easily install any 35 mm (0.79") equipment in a 19 in. network or server cabinet
- Depth-adjustable on eight levels from 48 to 174 mm (1.89 to 6.85 in.) to accommodate a wide range of products
- Ideal for DIN-rail equipment like industrial PoE switches, media converters, power supplies, circuit breakers, terminal blocks and more
- IEC 60297 / EIA 310-compliant; compatible with all standard 19 in. / 482.6 mm racks
- DIN-rail in accordance with IEC/EN 60715
- Heavy-duty construction with anodized 2 mm thick aluminum
- Maximum load capacity of 9 kg (20 lbs.)
- Includes 19" mounting material with four M6x12 screws, four M6 cage nuts, and four M6 plastic washers
- Three-year warranty

Specifications:

Standards and Certifications

- RoHS
- ANSI/EIA 310-E
- IEC 60297-3
- IEC/EN 60715

General

- Dimensions (D x W x H): 210 x 487 x 89 mm (8.27 x 19.17 x 3.5 in.); 2U
- Depth adjustment levels: 48/66/84/102/120/138/156/174 mm (1.9/2.6/3.3/4/4.7/5.4/6.1/6.9 in.)
- Net weight: 1.3 kg (2.87 lbs.)
- Gross weight: 1.55 kg (3.42 lbs.)
- Maximum load capacity: 9 kg (20 lbs.)
- Material: anodized aluminum, 2 mm
- Color: black

Package Contents

- Adjustable 19" Rackmount DIN Rail Enclosure, 2U
- DIN rail (installed)
- Cage nut set for 19" rackmount equipment (4 x M6x12 screw, 4 x M6x12 cage nut, 4 x plastic washer)
- Four M4x8 flat head screws

